



- Single- or double-sided
- Anodized aluminum case
- Polycarbonate side cover and hanger
- SMD LED application
- Status display with green and red LEDs
- Test switch
- Remote control and test with DALI interface
- High-temperature Ni-Cd battery cells
- Overcharge and deep discharge protection
- Transparent Plexiglas with screen printed
- Side lighting
- Ceiling mounted, ceiling recessed or wall mounted
- Optional - 110 VAC compatibility
- Optional - Metal hanger, hook or steel wire
- Optional - LiFePO4 or Ni-MH battery application



Please refer to "Pictogram Table" in Emergency Exit Luminaires Overview section of the catalogue for alternatives.

elco  
emergency lighting control

TECEE

DALI

CE

RoHS

LED

OSRAM  
LED Technology included

SELV

230 VAC  
50/60 Hz

IP 20

41  
ALU

GW  
850°C

FR4  
PCB

SMD

-III-  
Ni-Cd

EN  
60598-2-22

EN  
62386

In accordance with EN 60598-1, EN 60598-2-22, EN 62386 standards.

### TECHNICAL DATA

SUPPLY VOLTAGE :	230 VAC 50/60 Hz	SIGN DIMENSIONS :	180 x 299 mm
AMBIENT TEMPERATURE (ta) :	0 °C ... +40 °C	VIEWING DISTANCE :	36 m
RATED DURATION :	3 h	PROTECTION CLASS :	IP 20
BATTERY CHARGING TIME :	24 h	INSULATION CLASS :	I
BATTERY TYPE :	3,6 V Ni-Cd		

### LED INDICATION FUNCTIONS

Permanent GREEN	Charge mode
Fast flashing GREEN (0,1s on - 0,1s off)	Function test
Slow flashing GREEN (1s on - 1s off)	Duration test
Permanent RED	Load failure
Slow flashing RED (1s on - 1s off)	Battery failure
Fast flashing RED (0,1s on - 0,1s off)	Charging failure
Double pulsing GREEN	Inhibit mode
Binary transmission of address via GREEN/RED	Addressing or identification
GREEN and RED off	Emergency mode

### TEST SWITCH FUNCTIONS

Short press (<1s)	Starts the function test or terminate the all tests.
Long press (>5s)*	Starts the duration test.

\* The battery must be 100% full before the duration test can be started.

### PRODUCT LIST

PRODUCT CODE	RATED DURATION	OPERATING MODE*	LIGHT SOURCE	ROUTING MODE	TYPE OF MOUNTING
BYAL-L08/DALI-CY/SU	3 h	Maintained	12 x SMD LED	Double-sided	Surface Mounted - Plastic Hanger
BYAL-L08/DALI-CY/SUMA	3 h	Maintained	12 x SMD LED	Double-sided	Surface Mounted - Steel Wire
BYAL-L08/DALI-CY/MT	3 h	Maintained	12 x SMD LED	Double-sided	Surface Mounted - Metal Hanger
BYAL-L08/DALI-CY/SA	3 h	Maintained	12 x SMD LED	Double-sided	Recessed Mounted


\* Maintained: Lights on mains and stays alight in case of the mains failure.

### MAINS DATA


PRODUCT CODE	RATED POWER (W)*	MAINS CURRENT (A)*	POWER FACTOR (PF)*	DIMENSIONS (mm)	WEIGHT (kg)	QTY in CARTON BOX
BYAL-L08/DALI-CY/SU	4,82	0,032	0,63	40 x 304 x 235	0,700	1
BYAL-L08/DALI-CY/SUMA	4,82	0,032	0,63	40 x 304 x 235	0,700	1
BYAL-L08/DALI-CY/MT	4,82	0,032	0,63	40 x 304 x 235	0,700	1
BYAL-L08/DALI-CY/SA	4,82	0,032	0,63	102 x 372 x 235	1,255	1

\* Measured under 230 V mains.

### RECESSED MOUNTING HOLE SIZE



### TECHNICAL DRAWING / SURFACE MOUNTED



### TECHNICAL DRAWING / RECESSED MOUNTED

